



FABRICANTES DE
MOLINOS DE CAFÉ

MANUFACTURERS
OF COFFEE GRINDERS

Molino de café profesional
para todo tipo de cafés

Professional coffee grinder
for all types of coffee.

BRASIL CHROME SILVER / GOLD


COLLECTION CLASSIC

TECHNICAL CHARACTERISTICS 0-500gr/6' Max 2Kg

Voltage: 230V / 220V / 110V
Frequency: 50Hz / 60Hz
Phases: 1(monophase)
RPM: 1.300 / 1.600
Current: 1,4A / 3A
Capacitor: 9nf / 40nf
Power: 0,12 Hp / 275W
Protection rating: IP21
Motor supplied with thermal protector
Maximum operating time: 30 min.
Tempered steel grinding wheel (62HRC) ø 60mm
Lifespan of grinding wheels: 500kg
Hopper capacity: 1kg
Doser capacity: 300g
Doser regulation: 5/12g
Doser lever: right/left
Stop/start standard version: manual
Optional: automatic start
Dimensions width x length x height: 210x380x470mm
Weight: 8 kg
Air noise: 77dB
Diseñado bajo directiva 89/392 CE.



Grinding blades in tempered steel
(62HRC) ø 60mm.



CHROME SILVER CHROME GOLD



MAIN ATTRIBUTES

Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Body made of anti-scratch material, in a single piece (less vibrations, more robustness) with ventilation (internal air inlet and outlet) system. Bodywork finished in high-quality chrome (silver/gold). Large tray integrated into the body, ready to take knocks (portafilter). Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65HRC) 60mm in diameter.

Optional: Left- or right-handed doser lever. Coffee counter. Optional personalisation system with chrome plates on the doser and on the rear of the bodywork. Automatic stop/start every two cups (depending on filling dispenser).

