

## **FABRICANTES DE MOLINOS DE CAFÉ**

**MANUFACTURERS OF COFFEE GRINDERS**  Molino de café profesional para todo tipo de cafés

Professional coffee grinder for all types of coffee.

## JAMAICA "63dB"

OLLECTION SILENCER



## TECHNICAL CHARACTERISTICS 0-500gr/5' Max 3Kg

Voltage: 230V / 220V / 110V Frequency: 50Hz / 60Hz Phases: 1(monophase) RPM: 1.300 / 1.600 Current: 1.5A / 3.5A Capacitor: 8nf / 40nf Power: 0,25hp / 400W Protection rating: IP21 Motor supplied with thermal protector Maximum operating time: 30 min.

Tempered steel grinding wheel (62HRc) Ø 60mm

Lifespan of grinding wheels: 500kg Hopper capacity: 2kg

Doser capacity: 600g

Doser regulation: 5/12g

Doser lever: right/left

Stop/start standard version: automatic


Dimensions width x length x height: 210x380x660mm

Weight: 12kg

Air noise: 63dB

Diseñado bajo directiva 89/392 CE.













Hopper (2kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork made of stainless steel, with ventilation system (internal air inlet and outlet). Large tray integrated into the body, ready to take knocks (portafilter). Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65HRc) 60mm in diameter. Motor assembly with anti-vibration system. Silencer motor with internal autoventilation, 63dB.

Optional: Left- or right-handed doser lever. Coffee counter. Optional personalisation system with chrome plates on the doser and on the rear of the bodywork.